

U2V-100A USB to VGA-Audio Adapter



U2V-100A is a USB 3.0 projection screen VGA-Audio Adapter, which integrates USB 3.0 device controller, data transceiver module, VGA video and audio processing module. U2V-100A can display or expand the information on PC, smart phone and tablet to larger display devices through USB 3.0 interface, and supports the VGA video interface output. U2V-100A w/HDMI TX supports HPD & EDID & HDCP function. U2V-100A supports RGB/YUV video format, and the default maximum output resolution is 1920× 1080@60Hz. VGA TX video output resolution and audio format can be configured through software. U2V-100A provides multi-platform (Windows/Android/Mac OS) projection screen driver support. The output resolution is determined by the read VGA DDC information. When the DDC is not correctly parsed, the default output resolution list is as follows.

800×600@60Hz	1024×768@60Hz	1152×864@60Hz	1280×600@60Hz	1280×720@60Hz
1280×768@60Hz	1280×800@60Hz	1280×960@60Hz	1280×1024@60Hz	1360×768@60Hz
1366×768@60Hz	1400×1050@60Hz	1440×900@60Hz	1680×1050@60Hz	1920×1080@60Hz

HDMI/DVI TX : HDMI 1.4b compatible / Supports DDC / Supports VGA-Audio mode / Default max output resolution: 1920× 1080@60Hz

Audio: Default output 48KHz stereo

USB 3.0: Integrated USB 3.0 device / Compatible with USB 2.0 device mode / Integrated USB video and audio processing module.

OS Support : Windows 10 1607 or higher / Android 5.1 or higher / Mac OS 10.14 or higher
RoHS compliant / Applications: USB to VGA-Audio Projection Screen

- Easy to install , Plug & Play, Powers free
- Contents: USB3.0 A male to VGA Female with 15cm USB3.0 cable
- With Type-C male to USB3.0 A female adapter for Type-C (option)

