## SPL-118 HDMI to HDMI + USB3.0 Adapter



## Features & Specification

SPL-118 is HDIM 1 Port splitter & a USB 3.0 HD video and audio capture cable, which integrates USB 3.0 device controller, data transceiver module, video and audio processing module. SPL-118 can transmit the HDMI input audio and video signals to PC, Smart phone and tablet for preview or acquisition through USB 3.0 interface. SPL-118 output supports YUV422 and MJPEG modes, compatible with Windows, Android and Mac OS systems.

- HDMI RX: HDMI 1.4b compatible / Supports DVI 1.0 /Supports HDCP 1.4 / Supports RGB444, YCBCR422, YCBCR444, YCBCR420 color space / Supports deep color 24/30/36 bit mode.
  Supports CEA-861-E/CEA-861-F video format / Max input resolution: 4K(3840×2160@30Hz)
- Audio: USB audio default 48KHz stereo output / USB 3.0 / Integrated USB 3.0 device / Compatible with USB 2.0 device mode / USB video conforms to UVC1.0 specification / USB audio conforms to UAC1.0 specification
- USB video output : Supports both YUV422 and MJPEG modes /USB video output resolution / Default max resolution 1920× 1080@60Hz
- OS Support : Windows XP/7/8/10/11 / Android 5.0 or higher / Linux / Mac OS
- Applications
- High Definition Video Capture Card
- Security and Protection monitoring
- Medical Image
- HDMI-In => PC / Note Book / Smart phone / DVD Player & Host of HDMI-Out......
- USB-Out => PC / Note Book / Smart phone ........
- HDMI Out : In put Monitor
- Easy to install, Plug & Play, Powers free
- Contents: HDMI male to USB3.0 A male with 15Cm HDMI cable
- Weight: 40g include cable. Dimension: 46 \* 48 \*15 (mm) +15cm Cable.