

VGA +Audio to HDMI *2 Splitter



The VGA+ Audio to HDMI *2 Splitter can convert one Mini VGA & Audio signal to HDMI *2DVI signal sets support up to 2 different HDMI display terminals. Based on Cleared Edge technology, it supports up to 3.4Gbps data rate per channel, compliant with the HDMI 1.3 specification. This Splitter supports integrates EDID. Its HDMI Port 1.3 receiver supports configurable 1, 2 and 4 lanes @ 1.62Gbps, 2.7Gbps input, and supports up to 1080P output. Otherwise, the RGB triple-DAC supports up to 1080P@60Hz output.

- HDMI 1.3 specification compliant Support 3D video formats and 10810P extended resolution formats up to 3.4Gbps data rate VGA Support 1080P
- VGA Port input port to HDMI * 2 output ports
- Unlimited cascading for more output ports or signal repeating
- Power-saving modes by source-side disablement (using output enable) as well as sink-side detection (using Hot Plug Detect)
- Multiple display/TV support
- General / ESD protection up to 3 kV
- Cable distance: 5m (In or Out) /max.
- Operating temperature: 0°C ~ +70°C
- Power free(w/ Power Jack – USB Power Cable or DC Adapter Option)
- Weight: 40g include cable. Dimension: 46 * 48 *15 (mm) +15cm Cable.

Output port connection				EDID display
Output1	Connection	Output2	No connection	Output 1
Output1	No connection	Output2	Connection	Output 2
Output1	Connection	Output2	Connection	Output 2

-