

# AUM-200-MCL (Type-C to RS-232 Cable-DTE Mode w/LED\*9)

## Features:

- FTDI Chipset. The FT231X is a USB to serial UART interface with full modem control.
- Standard USB TO RS-232 Adapter. Power free / Bus powered. Easy to install , Plug & Play
- Fully compliant with USB Spec 3.X 2.0. Compliant USB Spec1.1.
- Driver support: Win-XP, WinXX, MAC OS.-X ,Linux, Android
- Connector: USB (Type C Male), RS232(DB9 Male)
- Data rate: Over 1000kbps. ESD Protection for RS-232 I/O' +/-15KV
- RS-232 for DTE Mode.
- With : Power / DCD / RXD / TXD / DTR / DSR / RTS / CTS / RI  
Power -- LED Red indicate, other – Red / Green LED indicate.  
Signal / TTL out 1 - LED appear Green (V-)  
Signal / TTL out 0 - LED appear Red (V+)
- With 1.0 meter Type-C cable
- When updating drivers, please refer to <http://www.ftdichip.com/FTDrivers.htm> ,
- RS-232 (DB-9 Male) with screws and nuts

## Specification:

### DB-9 Pin assignment

|      |       |     |     |
|------|-------|-----|-----|
| Pin1 | : DCD | <== | IN  |
| Pin2 | : RXD | <== | IN  |
| Pin3 | : TXD | ==> | OUT |
| Pin4 | : DTR | ==> | OUT |
| Pin5 | :     | GND |     |
| Pin6 | : DSR | <== | IN  |
| Pin7 | : RTS | ==> | OUT |
| Pin8 | : CTS | <== | IN  |
| Pin9 | : RI  | <== | IN  |

